

Serial No.10/761,132

Listing of Claims:

Claim 1 (currently amended) Apparatus to add weight to an athletic ball striking bat, having a handle and taper along the bat length, comprising in combination;

a) a sleeve sized to extend about the bat at the taper location,

b) the sleeve having associated retention means to effectively engage the bat at a zone along said taper to resist lengthwise removal of the sleeve off the bat during bat swinging,

c) weight means carried by the sleeve[[.]]_L

d) and including said bat and having a handle spaced endwise from the sleeve, the entirety of said retention means located endwise between said handle and the entirety of said weight means.

Claim 2 (currently amended) The combination of claim 1 wherein ~~the at least one~~ said weight means is carried at a location or locations spaced from said zone.

Serial No.10/761,132

Claim 3 (currently amended) The combination of claim 1 wherein the ~~at least one~~ weight means comprises a loose or flowable material comprising a granular substance such as metallic steel shot, pebbles, beads, seeds, or sand.

Claim 4 (currently amended) The combination of claim 1 wherein the ~~the at least one~~ weight means is dispersed over a plurality of regions.

Claim 5 (original) The combination of claim 2 wherein said retention means has an arcuate interior surface to engage said zone at an arcuately spaced location.

Claim 6 (original) The combination of claim 1 wherein said retention means comprises a plurality of spaced apart retention members.

Claim 7 (currently amended) The combination of claim 1 wherein the ~~support~~ sleeve has at least one generally longitudinally extending expansion slit ~~slits to accommodate the expansion of the system for different sized implements.~~

Serial No.10/761,132

Claim 8 (original) The combination of claim 1 including said bat projecting through the sleeve.

Claim 9 (currently amended) The combination of claim [[2]] 8 wherein the entirety of said ~~bat has a handle portion that projects from the sleeve,~~ said zone is located between said handle ~~portion~~ and said weight ~~or weights~~ means.

Claim 10 (original) The combination of claim 1 wherein said sleeve is cylindrical.

Claim 11 (original) The combination of claim 10 wherein said associated means includes an annular retainer at the inner side of the sleeve, and which has an inner surface to engage the bat taper, said inner surface having a configuration which is generally cylindrical and tapered, lengthwise of the sleeve.

Claim 12 (currently amended) The combination of claim 11 including at least one pocket carried by the sleeve and receiving said ~~at least one~~ weight means.

Serial No.10/761,132

Claim 13 (original) The combination of claim 12 including a first device on the sleeve for pulling the sleeve along the bat during assembly of the sleeve to the bat.

Claim 14 (original) The combination of claim 13 including a second device on the sleeve for pulling the sleeve along the bat during disassembly of the sleeve off the bat.

Claim 15 (original) The combination of claim 13 wherein said device is a first loop at a location near the sleeve and that faces in the direction of sleeve assembly onto the bat.

Claim 16 (original) The combination of claim 13 wherein said second device is a loop at a location near the sleeve end that faces in the direction of sleeve disassembly off the bat.

Claim 17 (currently amended) The combination of claim 1 wherein said weight ~~or weights~~ means comprises a deformable mass or masses of material.

Serial No.10/761,132

Claim 18 (currently amended) The combination of claim ~~16~~ 17 wherein said material is metallic and granular.

Claim 19 (currently amended) The combination of claim ~~16~~ 12 wherein said at least one pocket is spaced about an axis defined by the sleeve.

Claim 20 (currently amended) The combination of claim 19 wherein said ~~at least one~~ weight means comprises a deformable mass of material.

Claim 21 (currently amended) The combination of claim 11 wherein said retainer inner surface ~~is~~ has conical shape.

Claim 22 (currently amended) The combination of claim 12 wherein said at least one pocket is sewn to a sleeve comprising a flexible material.

Claim 23 (currently amended) The combination of claim 1 wherein the sleeve has a resiliently expansible section to allow the sleeve to fit to a bat of larger diameter.

Claim 24 (original) The combination of claim 1 including an annular insert in the sleeve, at an end of the sleeve, to block inward bunching of the sleeve end, toward a bat zone.

Claim 25 (original) The combination of claim 1 wherein the insert is proximate the retainer, and consists of lightweight material.

Claim 26 (original) The method of affixing a sleeve as defined in claim 1 that includes the following steps

- i) relatively advancing the sleeve in a first direction onto said bat to position said associated means at said zone along the bat taper,
- ii) practice swinging the bat, and
- iii) and subsequently relatively retracting the sleeve off the bat in second direction opposite the first direction.

Serial No.10/761,132

Claim 27 (original) The combination of claim 1 wherein the sleeve includes inner and outer sleeves, the inner sleeve having a wall that acts as a protector, for the bat.

Claim 28 (original) The combination of claim 1 wherein the retention means includes a retainer carried by the sleeve.

Claim 29 (original) The combination of claim 1 wherein the retention means includes a retainer carried by a pocket on a sleeve.

Claim 30 (currently amended) The combination of claim 1 including a frame carried by the sleeve, the weight ~~or weights~~ means carried by the frame.

Claim 31 (currently amended) The combination of claim 1 wherein the sleeve has an end portion defined by flaps which are edge connected to form a reduced diameter sleeve section to closely fit about a bat narrowed ~~sections~~ section.

Serial No.10/761,132

Claim 32 (original) The combination of claim 1 wherein the sleeve has two sections, one of larger diameter or diameters than the other.

Claim 33 (currently amended) The combination of claim 1 including additional means associated with the weight ~~or weights~~ means to enable selective weight removal or detachment from the sleeve.

Claim 34 (original) The combination of claim 1 wherein the sleeve has inner and outer sections, the sleeve inner section being semi-rigid.

Claim 35 (currently amended) A weighting device for use on an athletic ball striker as during swinging of the striker, and including the striker in the form of a baseball bat having a ball striking portion and handle, comprising in combination:

- a) an elongated receptacle having an opening via which the striker ball striking portion is received into the receptacle, with the handle projecting from the receptacle,
- b) a retainer carried on the receptacle for retaining the receptacle in generally enclosing relation to the striker,

c) there being weight material disposed at annular locations about an axis defined by the striker, and structure disposed about the striker holding said weight material in position relative to the striker[[.]]_L

d) and including said bat having said handle, the entirety of said retainer located endwise of the bat, between said handle and the entirety of said weight material.

Claim 36 (original) The combination of claim 35 wherein said structure includes a pocket or pockets spaced about the bat and in which said weight material is held at said annular spaced locations.

claim 37 (original) The combination of claim 1 wherein said at least one weight is disposed at an annular location about an axis defined by the bat, there being holder structure disposed about the bat holding said weight material in position relative to the bat.

Claim 38 (currently amended) A method for fabricating a swinging sport weighted implement practice comprising the following steps:

- a) sewing an inner wall comprising a fabric layer;
- b) inserting a bag of a weighted material into the fabric;
- c) applying a rubber coated retainer to the fabric, the entirety of the retainer spaced endwise from the weighted material;
- d) applying a layer of a foam;
- e) attaching a plurality of cross straps over the foam for added support; and
- f) applying at least one additional outer layer comprising a fabric.

Claim 39 (original) The method of claim 38 further comprising the step of applying an additional layer of a foam.

Claim 40 (original) The method of claim 39 further comprising the step of applying an additional fabric layer.

Serial No.10/761,132

Claim 41 (original) The method of claim 40 comprising the step of applying an additional plastic shield.

Claim 42 (currently amended) A weighting device for use on an athletic striker comprising a donut shaped member having an outer fabric casing, an inner fabric casing and being filled with a flowable weight material[[.]], said member having an inner locus of engagement with the striker, and said weight material spaced from said locus to receive pulling force in a direction away from said locus, as the striker is swung.

Claim 43 (new) A weighting device for use on an athletic ball striker as during swinging of the striker, and including the striker having a handle, comprising in combination:

a) a receptacle having an opening via which the striker ball striking portion is receivable into the receptacle, with the handle projecting from the receptacle,

b) a retainer positioned for retaining the receptacle to the striker ball striking portion,

c) and weighting structure carried by the receptacle to add substantial weight to the striker, for use as in striker practice swinging,

d) said retainer including a holder that is applied in a retaining position proximate a local portion of the receptacle, to effect retention of the receptacle to the striker during said practice swinging, substantially the entirety of said holder located between the handle and said weighting structure whereby pulling forces exerted via the weighting structure and via the receptacle are well distributed to said holder via the receptacle, during said practice swinging,

e) said retainer having coating, and located at the side of fabric, that receives loading transmitted by said weighting structure, said coating consisting of one of the following:

- i) rubber,
- ii) foam.